



### FEATURES & STANDARDS

- Industry leading warranty (24 months\*)
- Aluminium Die-Cast Construction.
- Provide accurate visual and electrical indication of valve positions.
- Weather-Proof to IP-67 Certified by ARAI
- Explosion-Proof to II-A ,II-B certified by CMRI
- Can be installed directly on the actuator thus reducing overall height.
- Least count in angular positioning is zero degree.
- LSB dome is provides higher visibility and manufactured out of high quality ABS plastic.
- Double Conduit entry 3 x PG 13.5 [1/2" NPT (F) or M20 x 1.5 as option] with 6 point high quality UL approved rugged terminal strip. Additional two terminal are provided for solenoid valve termination as standard.
- Underwriter Laboratory (USA) approved PCB with multiple switch options.
- Suitable for Namur V3 mountings sensors & switches.
- Inner dome available in RED-YELLOW & RED & GREEN
- Polyester Powder coating salt spray tested for atleast 500 hour.
- Two grounding terminal provide LSB body for static discharge.
- LSB body design to accommodate a wide variety of switches , sensors , cylindrical sensors.



ITEM	DESCRIPTIONS
1	BOTTOM BODY
2	TOP BODY
3	OUTER DOME
4	INNER DOME
5	DOMELOCK NUT
6	TOP DOME 'O' RING
7	SPINDLE

ITEM	DESCRIPTIONS
8	SPINDLE 'O' RING
9	CIRCLIP
10	BOTTOM CAM
11	TOP CAM
12	CAM NUT
13	CONNECTOR
14	PCB

ITEM	SENSOR/ SWITCH DETAILS
1	PCB
2	NJ2-V3-N
3	NBB3-V3-Z4
4	SJ3.5-N
5	SJ3.5-SN
6	NBB5-18GM60-WS
7	NBN4-12GM5-E2
8	NBN4-12GM40-Z0
9	NJ-5-18GM-N
10	NJ-8-18GM-N
11	NBN3-8GM30-E2-5M

ITEM	DESCRIPTIONS
15	EARTHING BOLT
16	SWITCH SCREW
17	SWITCH / SENSOR
18	SWITCH BOX END CAP
19	PHILIPS HEAD SCREW
20	MOUNTING PAD
21	BOTTOM 'O' RING

**NOTE:** Drawings are representative, please contact Sankey Controls for specific and current PDF drawings.  
 \*Sankey limited warranty of 24 months from date of shipment or 18 months from the date of start-up.  
 \*\* Other materials available upon request.